



UNIVERSAL CLEANING SOLUTIONS



ETL
C-Listed US
ETL Certified to
UL 1776 Standards
and to CSA

5600/5700 Series

Hot-Water Pressure Washers

Up to 8 GPM @ 3000 PSI

■ **50-ft. length of high-pressure hose** for ease in cleaning around a large area.

■ **Upright burner** delivers high efficiency and maintains constant temperature using oil, natural gas or LP.

■ **Pressure-relief valve** protects the machine and user.

■ **15HP with 208V, 230V or 460V, 3PH electric motor**, which is drip proof and comes with thermal overload protection and a manual reset; or **24 HP Honda gasoline engine**.



■ **Hotsy triplex, positive-displacement pump** carries seven-year crankcase and lifetime manifold warranties.

■ **Adjustable upstream detergent injection** ensures high-pressure sudsing for better cleaning.

■ **Simple, easy-to-use control panel** includes adjustable temperature control with precision safety controls.



Model 5732-4
natural gas-fired

■ **Quick disconnect stainless-steel nozzles** are color-coded for quick and easy changing between 0°, 15°, 40° spray nozzles.

■ **Float tank** helps maintain constant pressure and flow and helps prevent sediment from entering the machine's components. A great feature for use in well-water environments and low-water situations.

■ **Wheel kit and handle** (optional) makes for easy portability. **Pneumatic wheels** for easy maneuvering (shown on back).



Model 5645 shown with optional wheel kit.

Hotsy's 5600/5700 Series combines big water volume with high pressure and rugged construction for a bullet-proof industrial cleaning machine.

The value-packed 5600 and 5700 Series includes 7 models, giving you a broad choice of heavy-duty machines for your toughest cleaning tasks. The oil-fired Model 5645, powered by a Honda gasoline engine,

offers 6 GPM, 3000 PSI performance, while the electric-motor powered 5700 Series provides 8 GPM at 3000 PSI using oil, natural gas or optional LP-gas fuel. These are rugged machines with the power to blast away dirt, grease and grime under the toughest conditions.

Discover Hotsy's no-cost benefits

Choose the 5600/5700 Series for its high performance and reliability. Then enjoy the benefits of doing business with the leader in industrial cleaning equipment. You'll find more than 120 models of pressure washers to choose from, free on-site demos, factory-trained service people, pre-delivery dealer prep, on-site machine check-out, operator training, local parts and accessory inventory and an unbeatable warranty program.

Accessories to match your application

Hotsy's custom accessories tailor the 5600/5700 Series pressure washer to fit your specific requirements making your cleaning jobs faster, easier and more efficient. Choose from extra hose lengths, hose reels, wand extensions, thermal shut-down kit, quick couplers, downstream detergent injector, foam applicator, wet sandblaster, rotating brush and more.



Clean better with Hotsy detergents

Hotsy's broad selection of biodegradable detergents are formulated specifically for high-temperature, high-pressure cleaning. This means you get the best results from your Hotsy pressure washer while continuously protecting the machine. Exclusive advanced-formula Hotsy Continuous Clean (HCC) additives continuously clean the lime and mineral buildup that can occur in your washer's coil and fittings. This cleaning action reduces replacement costs and improves machine performance. Most Hotsy detergents are USDA and Canadian Agriculture approved. And they're concentrated, so a little goes a long way.

Call today for a demo!

Find out for yourself why the Hotsy 5600/5700 Series is right for your cleaning jobs. Call your Hotsy distributor today for all the details and a FREE on-site demo.



5600/5700 Series Specifications

5645†:	6 GPM @ 3000 PSI; 24 HP electric-start Honda gasoline engine; 740,000 BTU/hr. oil-fired water heater; shipping weight 1,200 lbs.
S5730-5:	8 GPM @ 3000 PSI; 15 HP, 208V, 3 PH electric motor; belt-drive pump, 740,000 BTU/hr. oil-fired water heater; shipping weight 1,060 lbs.
S5730-3:	8 GPM @ 3000 PSI; 15 HP, 230V, 3 PH electric motor; belt-drive pump, 740,000 BTU/hr. oil-fired water heater; shipping weight 1,060 lbs.
S5732-5:	8 GPM @ 3000 PSI; 15 HP, 208V, 3 PH electric motor; belt-drive pump, 657,000 BTU/hr. natural gas-fired water heater (LP gas-fired optional); shipping weight 985 lbs.
S5732-4:	8 GPM @ 3000 PSI; 15 HP, 230V, 3 PH electric motor; belt-drive pump, 657,000 BTU/hr. natural gas-fired water heater (LP gas-fired optional); shipping weight 985 lbs.
S5733-1:	8 GPM @ 3000 PSI; 15 HP, 460V, 3 PH electric motor; belt-drive pump, 740,000 BTU/hr. oil-fired water heater; shipping weight 1,070 lbs.
S5735-3:	8 GPM @ 3000 PSI; 15 HP, 460V, 3 PH electric motor; belt-drive pump, 657,000 BTU/hr. natural gas-fired water heater (LP gas-fired optional); shipping weight 990 lbs.

SPECIFICATIONS

Water Pump Volume:	5645: 6 GPM (22.7 lpm); 360 GPH (1362 lph) 5700 Series: 8 GPM (30.28 lpm); 480 GPH (1,816.7 lph)
Water Pump Pressure:	3000 PSI (207 bar)
Water Pump:	Hotsy triplex, positive displacement pump; ceramic plungers; brass manifold; oil-bath crankcase.
Pump Drives:	5645: 24 HP Honda gasoline engine,* electric start, battery required (not supplied), alternator included. 11.5 gallon, removable, rust-proof, polyethylene gas tank (red) and fuel-oil tank (black) with fuel gauge in caps. 5700 Electric Models: See series specifications above.
Oil-Fired Water Heater:	740,000 BTU/hr. UL-listed burner, pressure-atomizing type, with automatic electronic ignition. Choice of #1 or #2 diesel fuel, kerosene or #1 home heating oil as fuel. Fuel filter standard, 17-gallon fuel-oil tank; 11.5 gallon on Model 5645.
Gas-Fired Water Heater:	657,000 BTU/hr. AGA-listed gas controls; ring-type burner with aspirating spuds; natural draft; natural gas standard; LP gas optional.
Heating Coil:	Schedule 80, ASTM A53 close coiling pipe; hydrostatic pressure tested; vertically fired. Heating coil is sheathed in a full-length sheet-metal wrap. Equipped with an independently welded heat-retention baffle plate.
Stack Size (Diameter):	10" oil-fired; 10" gas-fired (gas-fired units require draft diverters).
Controls:	Adjustable temperature control, safety pressure relief valve, pressure switch, ON/OFF electric-motor switch, ON/OFF water-heater switch, detergent valve, motor-overload relay and automatic anti-rusting float valve.
Float Tank:	Removable, rust-proof polyethylene.
Wand Assembly:	Trigger-gun control with cool grip, quick coupled to a heavy-duty wand with insulated grip.
Nozzle:	Three stainless-steel nozzles: 0°, 15° and 40°
Hose:	1/2" ID, 50 ft., wire braid, 3500 PSI working pressure; burst pressure is at least 4 times working pressure; oil and chemical resistant. Swivel fittings on both ends.
Portability:	Optional
Alternator:	Standard with gasoline engine. Provides 115V power to the burner.
Optional Accessories:	Thermal shut-down kit, multiple-gun operation, extra hose lengths, hose reels, wand extensions, quick couplers, downstream detergent injector, wet sandblaster, rotating brush and foam applicator.
Construction:	Heavy-gauge steel; angle-iron frame.
Finish:	High-gloss powder coat.
Dimensions:	5645: L-64" (162.6 cm); W-32" (81 cm); H-55" (139.7 cm) 5700 Series: L-57" (145 cm); W-32" (81 cm); H-50" (127 cm)

*Engine performance may vary with high altitudes. This may affect output volume and pressure.
† ETL Certification pending



21 Inverness Way East, Englewood, Colorado 80112-5796 Built with PRIDE
Tel: (303) 792-5200 1-800-525-1976 Fax: (303) 792-0547 in the USA
e-mail: info@hotsy.com or visit our website: www.hotsy.com

P/N 768524B Printed in USA Effective 3/03 Supercedes 768524A (8/01)
Specifications and product descriptions subject to change without notice.
© 2003 Hotsy

America's #1 Manufacturer of Cleaning Systems

